

- 酚醛树脂制，具有优良的耐久性。
- 七角形是手感舒适的理想外形。


## ● 材质、表面处理



	KSF-PF
旋钮	酚醛树脂(黑)
螺纹部	钢*1 三价铬酸盐处理

\*1: [KSF-20-M4-PF]为黄铜。

单位: mm

型号 	D	M(粗牙)		Lf min.	H	s	d	质量(g)
		螺纹公称直径	螺距					
KSF-20-M4-PF	20	M4	0.7	6.5	13	7	10	3
KSF-25-M5-PF	25	M5	0.8	9.5	16	8	12	7
KSF-32-M6-PF	32	M6	1	12	20	10	14	12
KSF-40-M6-PF	40	M6	1	12	25	13	18	22
KSF-40-M8-PF	40	M8	1.25	14	25	13	18	20
KSF-50-M8-PF	50	M8	1.25	14	32	17	22	36
KSF-50-M10-PF	50	M10	1.5	18	32	17	22	41
KSF-63-M10-PF	63	M10	1.5	18	40	21	26	70
KSF-63-M12-PF	63	M12	1.75	22	40	21	26	80
KSF-80-M12-PF	80	M12	1.75	22	50	25	35	146
KSF-80-M16-PF	80	M16	2	30	50	25	35	160

## ● 型号指定

## KSF-32-M6-PF



 无尘洗净·无尘包装 → P.xxxx	 螺纹组合 → P.xxxx	 螺纹切割 → P.xxxx	 防松动 → P.xxxx	 激光刻印 → P.xxxx
不可对应	可对应, 费用另计	不可对应	不可对应	可对应, 费用另计