


● 材质、表面处理



| | |
|----|---------------------|
| | KSFS-M-A4-HP |
| 主体 | 相当于SUS316 研磨 |

- 耐腐蚀性尤其出色的内螺纹型七角形旋钮，采用相当于SUS316的全不锈钢制成。
- 七角形是手感舒适的理想外形。
- 形状凹凸少且经过表面研磨，清扫性优良。

单位：mm

| 型号  | D | M (粗牙) | | Lf | H | s | d | 质量 (g) |
|--|----|--------|------|----|----|----|----|--------|
| | | 螺纹公称直径 | 螺距 | | | | | |
| KSFS-32-M6-A4-HP | 32 | M6 | 1 | 12 | 20 | 9 | 12 | 55 |
| KSFS-40-M8-A4-HP | 40 | M8 | 1.25 | 15 | 25 | 12 | 14 | 103 |
| KSFS-50-M10-A4-HP | 50 | M10 | 1.5 | 18 | 32 | 15 | 18 | 209 |
| KSFS-63-M12-A4-HP | 63 | M12 | 1.75 | 22 | 40 | 19 | 20 | 378 |

● 型号指定

KSFS-32-M6-A4-HP

| | | | | |
|--|---|---|--|---|
|  无尘洗净·无尘包装 → P.xxxx |  螺纹组合 → P.xxxx |  螺纹切割 → P.xxxx |  防松动 → P.xxxx |  激光刻印 → P.xxxx |
| 欢迎洽询 | 可对应, 费用另计 | 不可对应 | 不可对应 | 可对应, 费用另计 |