



- 带塑料垫的调平调节器。
- 螺纹采用钢制。耐久性优良。
- 垫最大可倾斜15°。适用于倾斜面。

## ● 材质、表面处理



	FCM
螺丝	钢 三价铬酸盐处理
垫	玻璃纤维增强尼龙6 (亚光黑)
锁定螺母	钢 三价铬酸盐处理



## 尺寸

单位: mm

型号	D	M(粗牙)		H	h	sw1	sw2	L1	静态容许载荷*1 (N)	质量 (g)
		螺纹公称直径	螺距							
FCM-25-M6	25	M6	1	18.5	4	12	10	5.2	5000	26 - 30
FCM-25-M8	25	M8	1.25	18.5	4	12	13	6.8	5000	35 - 43
FCM-25-M10	25	M10	1.5	18.5	4	12	16	8.4	5000	50 - 60
FCM-32-M8	32	M8	1.25	22.5	5	12	13	6.8	7000	35 - 44
FCM-32-M10	32	M10	1.5	22.5	5	15	16	8.4	7000	64 - 80
FCM-32-M12	32	M12	1.75	22.5	5	15	18	10.8	7000	87 - 110
FCM-40-M8	40	M8	1.25	25.5	6	15	13	6.8	10000	50 - 64
FCM-40-M10	40	M10	1.5	25.5	6	15	16	8.4	10000	70 - 81
FCM-40-M12	40	M12	1.75	25.5	6	17	18	10.8	10000	104 - 134
FCM-50-M8	50	M8	1.25	27.5	7	15	13	6.8	10000	60 - 75
FCM-50-M10	50	M10	1.5	27.5	7	15	16	8.4	10000	76 - 90
FCM-50-M12	50	M12	1.75	27.5	7	17	18	10.8	10000	112 - 138
FCM-50-M16	50	M16	2	27.5	7	17	24	14.8	10000	168 - 220
FCM-60-M10	60	M10	1.5	35.5	8.5	17	16	8.4	14000	83 - 105
FCM-60-M12	60	M12	1.75	35.5	8.5	17	18	10.8	14000	122 - 150
FCM-60-M16	60	M16	2	35.5	8.5	24	24	14.8	14000	247 - 301
FCM-60-M20	60	M20	2.5	35.5	8.5	24	30	18	14000	371 - 490
FCM-60-M24	60	M24	3	35.5	8.5	24	36	21.5	14000	508 - 680

\*1: 表中数值为螺丝垂直于垫的状态下的值。在螺丝带角度的状态下, 会发生弯曲和屈曲应力, 导致静态容许载荷变小。  
表中数值非保证值, 仅供参考。

型号	Lm (mm)								
	40	50	63	80	98	100	125	138	158
FCM-25-M6	●	●	●						
FCM-25-M8	●	●	●						
FCM-25-M10		●	●	●					
FCM-32-M8	●	●	●						
FCM-32-M10		●	●	●					
FCM-32-M12			●	●		●			
FCM-40-M8		●	●	●					
FCM-40-M10		●	●	●					
FCM-40-M12			●	●		●			
FCM-50-M8		●	●	●					
FCM-50-M10		●	●	●					
FCM-50-M12			●	●		●			
FCM-50-M16			●	●		●			
FCM-60-M10		●	●	●					
FCM-60-M12			●	●		●			
FCM-60-M16				●		●	●		
FCM-60-M20					●			●	●
FCM-60-M24					●			●	●

- 型号指定

FCM-25-M8-40



② 螺纹长度Lm请从尺寸表中选择。

无尘洗净·无尘包装 → P.xxxx	螺纹切割 → P.xxxx	防松动 → P.xxxx	激光刻印 → P.xxxx
不可对应	欢迎洽询	不可对应	欢迎洽询