

- 便于操作的带旋钮锁销。
- 可快速进行工件的定位、固定。
- 为了防止从配合孔中脱落，请使用不锈钢钢球。具有耐久性。
- 根据剪切载荷大小的不同，备有标准型和重载型。重载型的剪切载荷为标准型的大约 1.5 倍。
- 可根据型号的末尾符号选择载荷类型。
无末尾符号—标准型
末尾符号 **[H]**—重载型

● 材质、表面处理

	PCBLS	PCBLS-H
旋钮	尼龙6	尼龙6
操作按钮	相当于SUS303	相当于SUS630
销	相当于SUS303	相当于SUS630
球	相当于SUS420J2	相当于SUS420J2
内置弹簧	不锈钢丝	不锈钢丝



● 为了与 **[PCBLS]** 区分，**[PCBLS-H]** 在销前端进行了槽加工。


尺寸

PCBLS 标准型 PCBLS-H 重载型

单位：mm

型号	d	d1	d2	L1	D	H	双面剪切载荷*1 (kN)	质量 (g)
PCBLS-5	5	5.5	16	6	30	26	14	16 - 26
PCBLS-6	6	7	16	7.1	30	26	21	17 - 31
PCBLS-8	8	9.5	19	8.2	35	32.5	38	38 - 71
PCBLS-10	10	12	19	9.6	35	32.5	60	45 - 107
PCBLS-12	12	14.5	25	10.6	42	39	87	93 - 179
PCBLS-16	16	19	25	14	42	39	155	140 - 324
PCBLS-5-H	5	5.5	16	6	30	26	24	16 - 26
PCBLS-6-H	6	7	16	7.1	30	26	35	17 - 31
PCBLS-8-H	8	9.5	19	8.2	35	32.5	63	38 - 71
PCBLS-10-H	10	12	19	9.6	35	32.5	100	45 - 107
PCBLS-12-H	12	14.5	25	10.6	42	39	144	93 - 179
PCBLS-16-H	16	19	25	14	42	39	257	140 - 324

*1：表中数值仅供参考，并非保证值。请考虑安全因素进行选择。
双面剪切载荷为截面有两面时的载荷。



无尘洗净·无尘包装 → P.xxxx	防松动 → P.xxxx	激光刻印 → P.xxxx
不可对应	不可对应	可对应，费用另计

PCBLS 标准型 PCBLS-H 重载型

型号	L (mm)																			
	10	15	20	25	30	35	40	45	50	60	70	80	90	100	110	120	130	140	150	
PCBLS-5	●	●	●	●	●	●	●	●	●	●	●	●								
PCBLS-6	●	●	●	●	●	●	●	●	●	●	●	●								
PCBLS-8	●	●	●	●	●	●	●	●	●	●	●	●	●	●						
PCBLS-10		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●				
PCBLS-12			●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
PCBLS-16				●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
PCBLS-5-H	●	●	●	●	●	●	●	●	●	●	●	●								
PCBLS-6-H	●	●	●	●	●	●	●	●	●	●	●	●								
PCBLS-8-H	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●					
PCBLS-10-H		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●			
PCBLS-12-H			●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
PCBLS-16-H				●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●

● 适用的锁销用链条


锁销型号	适用锁销用链条型号	通用锁销用链条型号			
		PBC → P.xxxx	PBCS → P.xxxx	PRC → P.xxxx	PSRC → P.xxxx
PCBLS-5	PCBLS-5-H				
PCBLS-6	PCBLS-6-H				
PCBLS-8	PCBLS-8-H				
PCBLS-10	PCBLS-10-H	PBC- *-14	PBCS- *-14	PRC- *-14	PSRC- *-14
PCBLS-12	PCBLS-12-H				
PCBLS-16	PCBLS-16-H				

● 锁销用链条的详情请参照各产品页。

● 相关产品

备有用于防止锁销丢失的各种锁销用链条、线缆和卷线。

- PBC PBCS → P.xxxx
- PRC → P.xxxx
- PSRC → P.xxxx



● 型号指定

PCBLS-10-40-H



销长度请从表中标有●的尺寸中选择。